

OPEN SPELTER SOCKET WITH PIN



Material	:	Cast steel
Working Load Limit	:	20% of the MBL
Finish	:	Painted or galvanised (< Type No. 100 standard galvanised)
Temperature Range	:	-40 °C up to +200 °C
Standard Certification	:	Certificate of Conformity 3.1 material certificate EN 10204

TYPE APPROVED PRODUCT
DNV•GL



SOCKETS

Sockets are Type Approved by DNVGL according DNVGL ST-0378



These sockets include our non-rotating system (NRS-system) which prevents the tump from turning or slipping out of the cone and guarantees a high performance connection.

Non-standard sizes or custom products available on request.



NR.	Rope Ø	Article number		MBL	A	B	C	ØD	ØD1	J	K	Weight
	mm	paint RAL 5013 blue	galvanised									
192	6-7	-	OSSP192G	8	52	39,5	33,5	8	17,5	17,5	8	0,4
194	8 - 10	-	OSSP194G	12	58	44,5	39,5	11	20,5	20,5	11	0,8
196	11 - 13	-	OSSP196G	20	63,5	51	49	14	25,5	25,5	12	1,3
198	14 - 16	-	OSSP198G	30	76,5	63,5	62	17,5	30	32	14	2,3
100	17 - 19	OSSP100P	OSSP100G	40	89	76	100	21	35	38	16	3,2
104	20 - 22	OSSP104P	OSSP104G	60	101	89	85,5	24	41	44	19	5
108	23 - 26	OSSP108P	OSSP108G	75	114	101	114	28	51	51	22	8,8
111	27 - 30	OSSP111P	OSSP111G	100	127	114	123,5	32	57	57	25	11,6
115	31 - 36	OSSP115P	OSSP115G	125	139	127	135	38	63	63	28	16,3
118	37 - 39	OSSP118P	OSSP118G	150	152	162	152	41	70	76	30	23,5
120	40 - 42	OSSP120P	OSSP120G	180	165	165	168	44	76	76	33	29
125	43 - 48	OSSP125P	OSSP125G	230	191	178	190	51	89	89	39	45
128	49 - 54	OSSP128P	OSSP128G	280	216	229	206	57	95	102	45	64,5
130	55 - 60	OSSP130P	OSSP130G	375	229	254	225	63	108	113	53	88
132	61 - 68	OSSP132P	OSSP132G	425	248	273	251	73	121	127	60	125
135	69 - 75	OSSP135P	OSSP135G	500	279	279	266	79	127	133	73	162
138	76 - 80	OSSP138P	OSSP138G	600	305	286	274	86	133	146	76	195
140	81 - 86	OSSP140P	OSSP140G	700	330	298	286	92	140	159	79	224
142	87 - 93	OSSP142P	OSSP142G	750	356	318	310	99	152	171	83	280
144	94 - 102	OSSP144P	OSSP144G	950	381	343	352	108	178	191	89	378
146	108 - 115	OSSP146P	OSSP146G	1200	460	480	430	125	190	208	101	564
150	122 - 130	OSSP150P	OSSP150G	1400	500	500	550	138	250	210	120	922
160	140 - 155	OSSP160P	OSSP160G	2000	580	500	590	160	275	230	140	1295
170	158 - 167	OSSP170P	OSSP170G	2500	675	600	640	175	290	310	160	1950